

BMP®51 Label Maker Specifications Sheet

www.bradyid.com.au/bmp51



BMP®51 Label Maker

The BMP®51 Label Maker has all the latest features for portable printing on the go: a large display screen, easy-to-use label design apps, fast print speed, and more. You can carry this printer throughout your facility to quickly and easily make labels on the go.

Plus, the BMP®51 Label Maker is a versatile portable printer with extensive connectivity and networking options. It offers built-in Bluetooth® technology or an optional wifi card, which means you can print wirelessly to this printer from your computer or Android phone.

Printer: Printer Name BMP®51 Label Maker Print Resolution Thermal transfer, 300 dpi Max Lines of Print 25 Print Speed 25.4mm/sec (1/sec) Keyboard Type QWERTY Dimensions 10.3" H x 6.0" W x 3.6" D (262 x 91 x 152 m Weight 2.6 lbs (1.2 kg) Warranty 2 Years Overmold/Rugged No Operating Temp 4° to 43° C (40° to 110° F) Humidity 20% to 90% (non-condensing) Storage Temp -18° to 43° C (0° to 110° F) Continuous or Die Cut Labels Continuous and die cut labels	nm)
Print Resolution Thermal transfer, 300 dpi Max Lines of Print 25 Print Speed 25.4mm/sec (1/sec) Keyboard Type QWERTY Dimensions 10.3" H x 6.0" W x 3.6" D (262 x 91 x 152 m Weight 2.6 lbs (1.2 kg) Warranty 2 Years Overmold/Rugged No Operating Temp 4° to 43° C (40° to 110° F) Humidity 20% to 90% (non-condensing) Storage Temp -18° to 43° C (0° to 110° F)	ım)
Max Lines of Print 25 Print Speed 25.4mm/sec (1/sec) Keyboard Type QWERTY Dimensions 10.3° H x 6.0° W x 3.6° D (262 x 91 x 152 m Weight 2.6 lbs (1.2 kg) Warranty 2 Years Overmold/Rugged No Operating Temp 4° to 43° C (40° to 110° F) Humidity 20% to 90% (non-condensing) Storage Temp -18° to 43° C (0° to 110° F)	ım)
Print Speed 25.4mm/sec (1/sec) Keyboard Type QWERTY Dimensions 10.3" H x 6.0" W x 3.6" D (262 x 91 x 152 m Weight 2.6 lbs (1.2 kg) Warranty 2 Years Overmold/Rugged No Operating Temp 4° to 43° C (40° to 110° F) Humidity 20% to 90% (non-condensing) Storage Temp -18° to 43° C (0° to 110° F)	nm)
Keyboard Type QWERTY Dimensions 10.3" H x 6.0" W x 3.6" D (262 x 91 x 152 m Weight 2.6 lbs (1.2 kg) Warranty 2 Years Overmold/Rugged No Operating Temp 4° to 43° C (40° to 110° F) Humidity 20% to 90% (non-condensing) Storage Temp -18° to 43° C (0° to 110° F)	ım)
Dimensions 10.3" H x 6.0" W x 3.6" D (262 x 91 x 152 m Weight 2.6 lbs (1.2 kg) Warranty 2 Years Overmold/Rugged No Operating Temp 4° to 43° C (40° to 110° F) Humidity 20% to 90% (non-condensing) Storage Temp -18° to 43° C (0° to 110° F)	nm)
Weight 2.6 lbs (1.2 kg) Warranty 2 Years Overmold/Rugged No Operating Temp 4° to 43° C (40° to 110° F) Humidity 20% to 90% (non-condensing) Storage Temp -18° to 43° C (0° to 110° F)	nm)
Warranty 2 Years Overmold/Rugged No Operating Temp 4° to 43° C (40° to 110° F) Humidity 20% to 90% (non-condensing) Storage Temp -18° to 43° C (0° to 110° F)	
Overmold/Rugged No Operating Temp 4° to 43° C (40° to 110° F) Humidity 20% to 90% (non-condensing) Storage Temp -18° to 43° C (0° to 110° F)	
Operating Temp 4° to 43° C (40° to 110° F) Humidity 20% to 90% (non-condensing) Storage Temp -18° to 43° C (0° to 110° F)	
Humidity 20% to 90% (non-condensing) Storage Temp -18° to 43° C (0° to 110° F)	
Storage Temp -18° to 43° C (0° to 110° F)	
3 1 , ,	
Continuous or Die Cut Labels Continuous and die cut labels	
Portability Yes	
Features:	
Memory 48 MB / Up to 25,000 Labels	
User Profiles No	
Cutter Type Manual	
Cut Options Cut between labels or at end of print job	
Label Retention After Cut Yes	
Labels Per Day (Average) 500	
Battery Life Indicator Yes	
Label Odometer (Supply Yes Remaining)	
Wearability Options Magnet attachment, soft carry case	
Drop Test Drop Tested: Six foot drop	
11: Danish, Dutch, English, Finnish, French Languages German, Italian, Norwegian, Portuguese, Spanish, Swedish	
Units Inches or Millimeters	Ι,

Power:	
Power Supply	AA Alkaline batteries (8), AC Power, or rechargeable lithium ion battery
Battery Included	Yes
Battery Life	1400 1" x 2" labels
Rechargeable Battery	Yes, Li-ion (2200 mAh)
Re-Charge Time (estimated)	3 hours
Charging Options	External and or internal via AC
Power Source Voltage	110-240
Auto Shut Off	10 minutes, user-configurable
Print Functions:	
Wire and Cable Wrap Mode	Yes
Cable Flag Mode	Yes
Terminal Block Mode	Yes
Patch Panel Mode	Yes
Circuit Breaker Mode	No
Banner (Landscape)	Yes
Banner (Portrait)	Yes
Print Preview	Yes
Multi-Label View	No
Customisable Library	No
Serialisation	Yes
Barcoding	39 & 128
Date/Time Stamp (Real Time Clock)	Yes
Fixed Length	Yes
Mirror Print	Yes, via software
Vertical Print	Yes
Reverse Print	Yes
Rotate Print	Yes
Auto Format	Yes
Text Justification	Horizontal: left, center or right Vertical: top, middle, bottom

Specifications subject to change without notice.

BMP®51 Label Maker Specifications (continued)

Print Functions: (continued)	
Multi-Copy Printing	Up to 99 Copies
Multi-Line Print	Yes
Frame Feature	Yes
Save Files	Yes
Display:	
LCD Type / Size	Custom LCD, 2.7" x 1.7" (68.58 mm x 43.18 mm)
LCD Resolution	320 x 240 pixels
LCD Characters	Font size dependent
LCD Backlight	Yes
Communication and Interface	
Connectivity:	Yes
PC Connectivity	USB, WiFi, LAN, Bluetooth
Import Data	Yes, with Labelmark® Software
Import Manufacturer Templates / Graphics	No
Software Compatibility	Labelmark®, Codesoft Software
Media:	
Туре	Cartridge
Load Labels Location	Тор
Label Output Location	Right Side
Compatible Media	M-, MC-, MC1- Series Cartridges (all sizes)
Memory in Cartridge	Yes
Maximum Print Width	1.44" (36.6 mm)
Maximum Print Length	39.00" (990 mm)
Maximum Liner Width	1.81" (46.0 mm)

Media Widths	Various sizes from 0.235" to 1.50" (6.4 mm x 38.1 mm)
Included Media	MC-1500-595-WT-BK 1.5" (38.1mm) Black on White Vinyl Tape
Number of Stock Parts	200+
Colour Print Capability	Single print colour on a label
Available Media Colours	Black on: White, Clear, Yellow, Orange, Silver White on: Clear, Red, Blue, Green, or Black Red on: White
Cartridge Width Detection	Yes
Cartridge Setting Detection	Yes
Custom Labels Available	Yes
Compliance	
Agency Approvals	FCC Class A, ICES003
RoHS compatibility	Pass
Patents	One or more patents apply including: US D692048, US 8395647, 6929415, 5951177, 5918989. Additional patents pending.
Trade	Harmonization Code (HTS Schedule A or B) /844.39.9000; Country of Origin: Malaysia (printer); ECCN: EAR99
MSDS	For Battery MSDS visit www.bradyid.com.au
Fonts, Graphics, Symbols	
Text Sizes	4 to 103pt + autosizing
Number of Fonts	(2) Brady Alpine and Brady Fixed Width
Number of Symbols	450
Special Characters	123
Symbol Categories	Arrows, Datacomm, Electrical, Exit, Fire, First Aid, CLP/GHS, Greek, HSID, International, Laboratory, Mandatory, Misc, Packaging, PPE, Prohibition, Public Info, Safety, Warning, WHMIS

BMP®51 Label Printer Media Offering

B-422 Adhesive Polyester	~
B-109 Polyethylene Tag	~
B-342 Permasleeve® Heat Shrinking Tube	V
B-351 Tamper-Evident Vinyl	V
B-412 Polypropylene Tag	~
B-425 Permanent Polypropylene	V
B-427 Self Laminating Vinyl	~
B-428 Metalized Polyester	V
B-461 Self Laminating Polyester	V
B-481 Stainerbondz™ Labels	~

B-482 Tissue Cassette Polyester	V
B-483 Ultra Aggressive Polyester	~
B-488 High Performance Polyester	V
B-490 Freezerbondz™ Labels	V
B-492 Freezerbondz™ 2 Labels	V
B-498 Repositionable Vinyl Cloth	V
B-499 Nylon Cloth	V
B-584 Reflective Tape	V
B-595 Indoor/Outdoor Vinyl	V



Compatible Media:

u.75 (19.05mm) height

For more information on the BMP®51 Label Maker and media, visit:

www.bradyid.com.au/bmp51

Brady Australia Pty Ltd 1800 620 816 www.bradyid.com.au

